

DRAG FACTOR UNCERTAINTY QUICK-REFERENCE MATRIX

Methodology, Instructions for Use, Limitations, and Disclaimer

Prepared by: Jinger Fuller, ACTAR Accredited

JFuller Consulting LLC | 2026

1. Purpose and Methodology

The Drag Factor Uncertainty Quick-Reference Matrix was developed to illustrate and quantify how variation within a selected drag-factor interval can affect calculated speed estimates over varying distances. The matrix was developed using Monte Carlo simulation to evaluate the potential variation in calculated speeds resulting from different drag-factor values within defined intervals.

The analysis evaluated 24 drag-factor intervals, beginning at 0.01–0.05 and continuing in increments of 0.05 through 1.15–1.20. Distances were evaluated in 10-foot increments from 10 feet through 250 feet. Approximately nine million simulation iterations were performed, with 15,000 iterations for each combination of drag-factor interval and distance.

For each simulation, a drag-factor value was sampled from within the applicable interval using a uniform distribution. The sampled value was then used to calculate a corresponding speed for the specified distance using the speed-distance-drag factor relationship:

$$\text{Speed (mph)} = \sqrt{(30 \times \text{drag factor} \times \text{distance in feet})}$$

The resulting speed values were compiled and statistically evaluated for each combination of distance and drag-factor interval. The resulting matrix reports four statistical measures: mean speed, speed range, standard deviation, and relative uncertainty.

Mean Speed represents the arithmetic average of the calculated speeds produced by the simulations within a particular distance and drag-factor interval.

Speed Range represents the difference between the maximum and minimum simulated speeds. It illustrates the spread of the calculated speed estimates produced by the sampled drag-factor values.

Standard Deviation describes the degree of dispersion of the simulated speed values around their mean. A larger standard deviation indicates greater absolute variation in the calculated speeds.

Relative Uncertainty expresses the standard deviation as a percentage of the mean speed. It is calculated as:

Relative Uncertainty (%) = (Standard Deviation ÷ Mean Speed) × 100

This measure provides a standardized way to describe the simulated speed variability relative to the mean speed for the selected interval.

The matrix is intended to demonstrate the mathematical relationship between drag-factor variation, distance, and calculated speed. It provides a consistent means of examining this relationship across numerous drag-factor intervals and distances without requiring the user to perform the individual calculations.

2. Instructions for Use

To use the matrix, first identify the distance associated with the calculation being evaluated. Next, identify the independently established drag-factor interval applicable to the analysis. Locate the intersection of the corresponding distance and drag-factor interval within the matrix.

The intersecting cells provide the simulated mean speed, speed range, standard deviation, and relative uncertainty associated with that combination.

The appropriate drag-factor interval must be established independently using the available physical evidence, scene conditions, testing, accepted reconstruction methodology, and other relevant case-specific information. The matrix does not determine which drag factor should be selected for a particular collision.

For example, if an independently supported drag-factor interval is 0.50–0.55 and the applicable distance is 100 feet, the user would locate the 100-foot section and the 0.50–0.55 drag-factor row. The values in the intersecting cells describe the statistical results of the simulations for that combination.

The results should be interpreted as an illustration of the speed variation associated with the modeled drag-factor interval, not as a definitive statement of the actual vehicle speed or the total uncertainty of a reconstruction.

If the measured distance falls between the distances represented in the matrix, the user should recognize that the displayed values correspond to the listed distance, not the exact measured distance. A more precise case-specific analysis should be performed when necessary rather than assuming that the nearest listed distance fully represents the measured condition.

3. Distance and Measurement Uncertainty

The distances shown in the matrix are generalized reference distances evaluated at fixed 10-foot increments. They are not intended to represent the exact measured distance in any particular collision investigation.

In an actual reconstruction, the distance used in a speed calculation is itself subject to potential measurement uncertainty. The uncertainty associated with the measured distance must be independently evaluated based on the evidence, measurement methods, scene conditions, equipment, and other relevant factors.

The matrix does not incorporate or account for the uncertainty associated with measuring the distance in an individual case. It also does not combine distance uncertainty with drag-factor uncertainty to produce a total uncertainty estimate.

Because calculated speed depends on both drag factor and distance, variation or uncertainty in either input can affect the resulting speed estimate. Accordingly, the values in the matrix represent the modeled effects of drag-factor variation at the specified distances and should not be interpreted as a complete uncertainty analysis for an actual collision.

Users should evaluate the uncertainty of each relevant input independently and determine whether a more comprehensive uncertainty analysis is appropriate for the circumstances of the case.

4. Limitations and Appropriate Application

This matrix is a supplemental technical reference intended for use by trained collision reconstructionists, investigators, engineers, and other qualified professionals. It is not a substitute for professional judgment, scene investigation, physical evidence evaluation, vehicle examination, appropriate testing, or accepted collision reconstruction methodology.

The results are dependent on the mathematical model, the selected drag-factor intervals, the uniform sampling distribution, the specified distances, and the simulation procedures used to generate the data. The statistical outputs describe the results of those simulations and do not independently establish that the selected drag-factor interval accurately represents a particular surface or collision event.

The matrix does not account for all factors that may influence an actual reconstruction, including uncertainty in distance measurements, grade, changes in surface conditions, braking characteristics, vehicle dynamics, measurement error, or other case-specific variables unless they are separately addressed in the reconstruction analysis.

The matrix should not be used as the sole basis for establishing a vehicle's speed, selecting a drag factor, determining causation, or reaching a forensic conclusion. Users are responsible for evaluating the applicability of the model and its assumptions to the specific circumstances under examination.

5. Disclaimer and Limitation of Responsibility

This matrix is provided for informational, educational, and supplemental technical reference purposes only. Although reasonable care has been exercised in developing the underlying analysis, no representation or warranty, express or implied, is made regarding the completeness, accuracy, applicability, or suitability of the matrix for any particular investigation, calculation, legal proceeding, or other purpose.

Use of this matrix is voluntary and at the user's own risk. The user is solely responsible for independently verifying the calculations, evaluating the assumptions and limitations, determining the appropriateness of the selected inputs, and interpreting the results in the context of the specific case.

Jinger Fuller and JFuller Consulting LLC disclaim responsibility, to the fullest extent permitted by applicable law, for errors, omissions, interpretations, conclusions, or improper applications arising from the use or misuse of this matrix. Neither the author nor JFuller Consulting LLC shall be responsible for decisions, opinions, reports, testimony, or other actions taken by users in reliance upon the matrix, subject to applicable law.

This disclaimer does not replace the user's professional obligations, applicable evidentiary standards, or the need for independent technical analysis. It is not intended to waive or exclude any liability that cannot lawfully be excluded.

Prepared by Jinger Fuller, ACTAR Accredited JFuller Consulting LLC 2026

Prepared by Jinger Fuller, ACTAR Accredited